



# Kofax Unified Client for Lexmark Technical Specifications

Version: 1.0.0

Date: 2024-08-09

**KOFAX**

© 2023-2024 Tungsten Automation. All rights reserved.

Tungsten and Tungsten Automation are trademarks of Tungsten Automation Corporation, registered in the U.S. and/or other countries. All other trademarks are the property of their respective owners. No part of this publication may be reproduced, stored, or transmitted in any form without the prior written permission of Tungsten Automation.

# Table of Contents

<b>Chapter 1: About the Unified Client for Lexmark.....</b>	<b>4</b>
<b>Chapter 2: Product requirements.....</b>	<b>5</b>
Product components.....	5
Supported card readers.....	6

## Chapter 1

# About the Unified Client for Lexmark

The Kofax Unified Client for Lexmark adds print and capture capabilities to Lexmark devices through AutoStore, Equitrac, and Output Manager while still using device-specific features.

Specific hardware and software compatibility requirements are outlined in this document. You must meet these requirements to support the Unified Client for Lexmark. These requirements specifically list the needs of the Unified Client for Lexmark and do not include any additional requirements for other components you might use in your system.

## Chapter 2

# Product requirements

## Product components

Specification	Description
Supported devices	<p>The Unified Client will function with the Lexmark MFP and SFP devices that support the eSF 6.2 framework with screen sizes of small, wide, and extra-large screens. Compatible branded Fujifilm, Sharp, Toshiba, and Xerox A4 devices are also supported.</p> <p>The Unified Client for Lexmark supports multifunction printer (MFP) and single-function printer (SFP) devices. MFP devices support print, scan, and copy functions. SFP only supports printing. See <a href="#">MFD and Productivity Supported Devices</a> for an updated list of specific models.</p>
Device firmware versions	Lexmark eSF 6.2, firmware 074.258.
Required third-party technologies	None
Compatible third-party technologies	A hard drive on the device is required.
Required Kofax software	<ul style="list-style-type: none"><li>• Device Registration Service (DRS)</li></ul>

Specification	Description
Compatible Kofax software	Compatible Kofax software with IPv6 functionality: <ul style="list-style-type: none"> <li>• ControlSuite 1.2 with fix pack 2 or later</li> <li>• AutoStore 8.2 with fix pack 2 or later</li> <li>• Equitrac 6.2 with fix pack 2 or later</li> <li>• Output Manager 5.2 with fix pack 2 or later</li> <li>• Business Connect 8.2 with fix pack 2 or later</li> </ul>
Supported languages	<ul style="list-style-type: none"> <li>• English</li> <li>• Czech</li> <li>• Dutch</li> <li>• Danish</li> <li>• French</li> <li>• Finnish</li> <li>• German</li> <li>• Hungarian</li> <li>• Italian</li> <li>• Japanese</li> <li>• Korean</li> <li>• Norwegian</li> <li>• Polish</li> <li>• Portuguese</li> <li>• Russian</li> <li>• Simplified Chinese</li> <li>• Spanish</li> <li>• Swedish</li> <li>• Traditional Chinese</li> <li>• Turkish</li> </ul>

## Supported card readers

The Unified Client for Lexmark supports the following card readers.

### **Kofax card readers**


- Kofax Micro Card Reader
- Kofax Equitrac ID Card Reader

The Unified Client for Lexmark has also been tested with the following card readers.

### **Third-party card readers**

- Elatec TWN3
- Elatec TWN4

- RFIDEas pcProx RDR-7L81xKU
- RFIDEas pcProx RDR-80581xKU
- HID Omnikey 5427

 When a third-party card reader is used, a third-party card reader license is required. Since January 2023, third-party card readers are provided free of charge for ControlSuite. Please ensure that licenses are available for the amount of card readers being used within the ControlSuite deployment.